



LED TREE RING LIGHT



■ Product Features

- Fully sealed, waterproof design utilizing silicone sealing materials.
- Ensures an ingress protection rating of IP65 or higher.
- High luminous efficacy and high color rendering index (CRI).
- High-transmittance PMMA optical lens with a beam uniformity greater than 0.92.

Address: Building 4, Beiguang Industrial Park, No. 269,
Liangbai Road, Longgang District, Shenzhen

Tel: +86 133 2280 6730

Email: sales@lummilight.com

Website: <https://www.lummilight.com>

LM-LH-BS-1001

Voltage: DC24V
Power : 12W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: 220*60mm
Material: aluminum + tempered glass
Waterproof rating: IP65
Control method: ON/OFF DMX512

LM-LH-BS-1002

Voltage: DC24V
Power : 18W/24W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: 268*60mm
Material: aluminum + tempered glass
Waterproof rating: IP65
Control method: ON/OFF DMX512

LM-LH-BS-1003

Voltage: DC24V
Power : 12W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: 245*70*52mm
Material: aluminum + PC cover
Waterproof rating: IP65
Control method: ON/OFF DMX512

LM-LH-BS-1004

Voltage: DC24V
Power : 12W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K
Beam angle: 10/15/25/30/45/60°
Size: 220*60mm
Material: aluminum + PC cover
Waterproof rating: IP65
Control method: ON/OFF

LM-LH-BS-1005

Voltage: DC24V
Power : 18*5W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K
Beam angle: 10/15/25/30/45/60°
Size: 550*400*270mm
Material: aluminum + tempered glass
Waterproof rating: IP65
Control method: ON/OFF

LM-LH-BS-1006

Voltage: DC24V
Power : 3W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K
Beam angle: 10/15/25/30/45/60°
Size: 108*35*81mm
Material: aluminum
Waterproof rating: IP65
Control method: ON/OFF

无限拼接

LM-LH-BS-1007

Voltage: DC24V
Power : 3W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K
Beam angle: 10/15/25/30/45/60°
Size: 96*40*66mm
Material: aluminum + tempered glass
Waterproof rating: IP65
Control method: ON/OFF

LM-LH-BS-1007

Voltage: DC24V
Power : 6W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K
Beam angle: 10/15/25/30/45/60°
Size: 120*60*130mm
Material: aluminum + tempered glass
Waterproof rating: IP65
Control method: ON/OFF

LM-LH-BS-1008

Voltage: DC24V
Power : 6W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: 170*46*190mm
Material: aluminum + PC cover
Waterproof rating: IP65
Control method: ON/OFF DMX512

LM-LH-BS-1008

Voltage: DC24V
Power : 12W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: 225*64*190mm
Material: aluminum + tempered glass
Waterproof rating: IP65
Control method: ON/OFF DMX512

LM-LH-BS-1009

Voltage: DC24V
Power : 18W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: 270*65*195mm
Material: aluminum + tempered glass
Waterproof rating: IP65
Control method: ON/OFF DMX512

LM-LH-BS-1009

Voltage: DC24V
Power : 24W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: 270*65*195mm
Material: aluminum+ tempered glass
Waterproof rating: IP65
Control method: ON/OFF DMX512

LM-LH-BS-2001

Voltage: DC24V/AC100~265V
 Power : 12W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: 225*62*152mm
 Material: aluminum + tempered glass
 Waterproof rating: IP65
 Control method: ON/OFF DMX512

LM-LH-BS-2001

Voltage: DC24V/AC100~265V
 Power : 12W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: 515*62*152mm
 Material: aluminum + tempered glass
 Waterproof rating: IP65
 Control method: ON/OFF DMX512

LM-LH-BS-2002

Voltage: DC24V/AC100~265V
 Power : 18W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: 270*65*150mm
 Material: aluminum + tempered glass
 Waterproof rating: IP65
 Control method: ON/OFF DMX512

LM-LH-BS-2002

Voltage: DC24V/AC100~265V
 Power : 24W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: 270*65*150mm
 Material: aluminum + tempered glass
 Waterproof rating: IP65
 Control method: ON/OFF DMX512

LM-LH-BS-2003

Voltage: DC24V
 Power : 12W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: 245*65*260mm
 Material: aluminum + tempered glass
 Waterproof rating: IP65
 Control method: ON/OFF DMX512

LM-LH-BS-2004

Voltage: DC24V
 Power : 5*18W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: 500*38*245mm
 Material: aluminum+ tempered glass
 Waterproof rating: IP65
 Control method: ON/OFF DMX512