



LED UNDERWATER LIGHT



Product Features

- Fully sealed, waterproof design utilizing silicone sealing materials.
- Ensures an ingress protection rating of IP65 or higher.
- High luminous efficacy and high color rendering index (CRI).
- High-transmittance PMMA optical lens with a beam uniformity greater than 0.92.

LED Underwater Light



LM-LH-SD-1001

Voltage: DC24V
Power : 3W/5W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: $\Phi 105 \times 155$ mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512




LM-LH-SD-1001

Voltage: DC24V
Power : 6W/7W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: $\Phi 120 \times 155$ mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512




LM-LH-SD-1001

Voltage: DC24V
Power : 9W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: $\Phi 145 \times 180$ mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512




LM-LH-SD-1001

Voltage: DC24V
Power : 12W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: Φ145*180mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512




LM-LH-SD-1001

Voltage: DC24V
Power : 15W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: Φ170*225mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512




LM-LH-SD-1001

Voltage: DC24V
Power : 18W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: Φ190*225mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512



LM-LH-SD-1001

Voltage: DC24V
Power : 24W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: Φ205*280mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512



LM-LH-SD-1001

Voltage: DC24V
Power : 36W
LED Brand: Bridgelux/Osram/CREE/Philips
Color: 2200K/2700K/3000K
4000K/6000K/RGB/RGBW
Beam angle: 10/15/25/30/45/60°
Size: Φ230*250mm
Material: Stainless steel + tempered glass
Waterproof rating: IP68
Control method: ON/OFF DMX512



LM-LH-SD-2001

Voltage: DC24V
 Power : 6W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ125*160mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512

LM-LH-SD-2001

Voltage: DC24V
 Power : 6W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ135*170mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512

LM-LH-SD-2001

Voltage: DC24V
 Power : 9W/12W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ160*180mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512

LM-LH-SD-2001

Voltage: DC24V
 Power : 12W/15W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ165*200mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512

LM-LH-SD-2001

Voltage: DC24V
 Power : 15W/18W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ190*200mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512

LM-LH-SD-2001

Voltage: DC24V
 Power : 18W/24W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ215*250mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512



LM-LH-SD-2001

Voltage: DC24V
 Power : 24W/36W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ235*280mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512



LM-LH-SD-2001

Voltage: DC24V
 Power : 24W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ250*H200mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512



LM-LH-SD-3001

Voltage: DC24V
 Power : 36W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ300*241mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512



LM-LH-SD-4001

Voltage: DC24V
 Power : 18W/24W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ210*H100mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512



LM-LH-SD-4001

Voltage: DC24V
 Power : 24W/36W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ240*H200mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512



LM-LH-SD-4001

Voltage: DC24V
 Power : 24W/36W
 LED Brand: Bridgelux/Osram/CREE/Philips
 Color: 2200K/2700K/3000K
 4000K/6000K/RGB/RGBW
 Beam angle: 10/15/25/30/45/60°
 Size: Φ200*H250mm
 Material: Stainless steel + tempered glass
 Waterproof rating: IP68
 Control method: ON/OFF DMX512